

Air Cored Solenoid – 700 Turns



EM0090-001 Solenoid 700 Turns

Description:

A simple solenoid wound with enamelled copper wire on a heat resistant former. Designed to be mounted on its end to stand vertical from the bench. Fitted with coloured insulated 4mm socket head spin free terminals for the connection of wires or banana plugs.

Specifications:

Number of turns (as marked on the former): 700 turns 0.9mm diameter enamelled copper.

Maximum steady current: 3 amps. Peak current (for up to 30 seconds maximum): 5 amps.

Caution:

During any experiment, be careful that the coil does not overheat during use. If the winding is too hot to touch with the hand, it means the coil internally will be overheated and it must be turned off immediately before damage occurs.

This instrument is normally used with other IEC apparatus such as 'Mass of Electron', 'Current Balance', 'Hall Effect' and other types of apparatus. The IEC Air Cored Solenoid can also be used for magnetising and demagnetising or other general purpose solenoid work.

Length: 167mm	Width: 68mm	Height: 77mm	Weight: 750g
---------------	-------------	--------------	--------------

Designed and manufactured in Australia

INDUSTRIAL EQUIPMENT & CONTROL PTY.LTD.

61-65 McClure St. Thornbury. 3071 Melbourne. Australia
Tel: 61 (0)3 9497 2555 Fax: 61 (0)3 9497 2166 www.iecpl.com.au