





Bottle Top Dispenser



Lasany is proud to offer its NEW BOTTLE TOP DISPENSERS which is an unique combination of affordable pricing and high performance.

Simple design clubbed with variety of useful features makes Lasany BOTTLE TOP DISPENSERS an obvious choice for all routine dispensing needs.

High precision and accuracy is ensured through several stages of strict quality checks during manufacturing process. Each instrument is individually calibrated in accordance with ISO 8655 standards and comes with individual calibration certificate.

SALIENT FEATURES

- Six model with adjustable volumes:
(a) 0.25-2.5ml (b) 0.5-5ml (c) 1-10ml (d) 2.5-30ml (e) 5-60ml (f) 10-100 ml.
- Easy to use, simple construction and good chemical compatibility.
- Each instrument comes with three adapters to fit in most of the laboratory Reagent bottles. Standard thread : 30mm
- Adapters : 28mm, 32mm, 36mm, 40mm and 45mm
- Smooth, effortless plunger movement.
- Safety discharge system reduces the risk of accidental dispensing.
- Nozzle cap prevent any unwanted drop on the work space.
- Instruments are fully autoclavable at 121°C, 15psi. Need for dis-assembling the instruments for autoclaving.
- Easy to dis-assemble for cleaning and servicing.
- In-lab, user re-calibration is possible in compliance with GLO/ISO Norms

Classic Models : Wetted parts are PP, borosilicate Glass and FEP. Suitable for routine laboratory application.

Research Models : All wetted parts are PTFE , FEP and borosilicate glass. Only this can be used for all laboratory reagent application.

PRODUCT SPECIFICATIONS

Piston	:	Polypropylene
Cylinder	:	Glass
Hosing	:	Polypropylene
Volume adjustments	:	Locking rocker switch
Valve assembly	:	Glass Ball & Seat
Discharge Assembly	:	Teflon
Delivery Tube	:	Polypropylene
Calibration	:	Individually calibrated and certified
Accuracy & reproducibility	:	In accordance with ISO 8655 standards
Compatibility	:	Excellent - suitable for most reagents except HF
Bottle Thread size	:	30mm
Additional Adaptors	:	28mm, 32mm, 36mm, 40mm and 45mm

SPECIFICATIONS

Classic Model	Research Model	Vol. Range	Increment	Accuracy ± % ± ml	CV ± % ± ml
LI-D1	LI-DR1	0.25 - 2.5 ml	0.05 ml	0.6 0.015	0.2 0.005
LI-D2	LI-DR2	0.5 - 5 ml	0.1 ml	0.5 0.025	0.1 0.005
LI-D3	LI-DR3	1 - 10 ml	0.2 ml	0.5 0.050	0.1 0.010
LI-D4	LI-DR4	2.5 - 30 ml	0.5 ml	0.5 0.150	0.1 0.030
LI-D5	LI-DR5	5 - 60 ml	1.0 ml	0.5 0.300	0.1 0.060
	LI-DR6	10 - 100 ml	2.0 ml	0.5 0.500	0.1 0.100

* Design & specifications are subject to change without any prior notice.

* O.E.M. Option available